

MZ-Series Industrial Scales

Ideal for shipping
and industrial
applications!

MZ-Series Features:

- Display can be wall-mounted and located 9-feet away from weighing platform
- Large, blue backlit liquid-crystal display with adjustable angles.
- Weigh units: kg, lbs, ozt (grams available on MZ-11A and MZ-22A).
- Count mode perfect for inventory and mailing operations
- Totalization application
- Removable stainless steel weighing platform
- 200% overload protection.
- AC or battery (9-volt) operation with battery saving mode
- RS-232 data interface to connect to printer or computer
- External calibration with three selectable weight values
- Power supply and RS232 cable included



AINSWORTH

Established 1880

1401 17th Street, Suite 750 ▪ Denver, Colorado 80202
303-431-7255 ▪ 1-800-321-1135 ▪ Fax 303-423-4831

MZ-Series Industrial Scales

Convenience and flexibility in high capacity weighing!

Diverse Design. Large, blue backlit liquid crystal display can be adjusted for best viewing angle. Display can be placed on countertop or wall-mounted up to 9-ft away from weighing platform.



Dynamic Platforms. Weighing capacities up to 200 kg (440 lbs) with 200% overload protection to protect against damage to weigh cell. Two different platform sizes for diverse weighing. Removable stainless steel weighing platform for easy clean up.

Battery or AC operation. Use the provided AC wall power supply when near power receptacles. Or battery power with a 9-volt battery (not included). To save battery life, select 4 or 10 minutes of inactivity for the scale to automatically power down.

Ideal for shipping and industrial applications. Toggle between kg and pounds with a single keypress (grams available on MZ-11A and MZ-22A). Count mode is perfect for inventory and mailing operations. Totalization application allows you to store up to 99 individual weights and then see the total weight.

Specifications

Model	MZ-11A	MZ-22A	MZ-55A	MZ-102A	MZ-205A
Capacity	10kg (22 lbs.)	20kg (44 lbs.)	50kg (110 lbs.)	100kg (220 lbs.)	200kg (440 lbs.)
Readability	1g (0.002 lbs.)	2g (0.004 lbs.)	5g (0.01 lbs.)	20g (0.04 lbs.)	50g (0.1 lbs.)
Taring Range	0 to 10kg	0 to 20kg	0 to 50kg	0 to 100kg	0 to 200kg
Repeatability	±2g	±4g	±10g	±40g	±100g
Linearity	±3g	±6g	±15g	±60g	±150g
Pan Size	12.4 x 12.4" (31 x 31 cm)	12.4 x 12.4" (31 x 31 cm)	12.4 x 12.4" (31 x 31 cm)	15.9 x 20.5" (40 x 52 cm)	15.9 x 20.5" (40 x 52 cm)
Net Weight	9.9 lbs. (4.4kg)	9.9 lbs. (4.4kg)	9.9 lbs. (4.4kg)	35.2 lbs. (16kg)	35.2 lbs. (16kg)

Common Specifications:

Stabilization Time (average):	2 sec.
Power Requirements:	AC adapter (included) or 9V battery
Operating Temperature:	10°C – 40°C (50°F – 104°F)
Storage Temperature:	-10°C – 70°C (14°F – 150°F)

AINSWORTH

Established 1880

1401 17th Street, Suite 750 ■ Denver, Colorado 80202
303-431-7255 ■ 1-800-321-1135 ■ Fax 303-423-4831